

profilan[®] - Wasserbasierende Oberflächenbeschichtung für das Handwerk
Water-based surface coatings for professionals



profilan[®]-prevent Imprägniergrund Impregnating primer



Water-based impregnating primer for wood used outdoors

Biocidal primer for the protection against blue stain, rot and insects according to DIN 68800 part 3. Efficacy certified according to DIN EN 113 and DIN EN 152-1.

Fields of application: For the protection against mould, blue stain and rot of wood used above ground and not statically loaded.

Properties:

- Deep, lasting protection
- Provides excellent adhesion of following coatings
- Odourless after drying

Consumption: 80 – 100 ml/m² per coat

Colours: 0000 Colourless

Pack size	VPE	Units per pallet (Product-No. W7022)
0.75 l tin	6	77 boxes
2.5 l tin	4	36 boxes
10 l drum	–	30 units
200 l drum	–	2 units

profilan[®]-secur Isolierlack Isolating primer and top coat



Water-based isolating primer for wood used in- and outdoors

White primer and intermediate coating with isolating properties against bleeding of tannins contained in wood.

Fields of application: For the priming of structural wood to be coated with water-based bright opaque paints.

Properties:

- Highly efficient against the bleeding of tannins contained in wood
- Quick drying
- High level of opacity
- Block resistant
- Excellent levelling properties

Consumption: 80 – 100 ml/m² per coat

Colours: 9110 White

Pack size	VPE	Units per pallet (Product-No. W7002)
0.75 l tin	6	77 boxes
2.5 l tin	4	36 boxes
10 l drum	–	30 units
20 l drum	–	22 units

profilan[®]-fina-Hybrid Dünnschichtlasur Low build wood stain



Water-based low build wood stain with high UV protection for wood used in- and outdoors

Transparent wood stain which enhances the natural grain of timber. Protection against mould and algae.

Fields of application: For all wooden elements, e.g. wall and ceiling panelling, doors, shelves, soffits, boarding, pergolas, balcony railings, etc.

Properties:

- Optimised flow properties
- Moisture regulating
- Low grain raising
- Breathable
- Dries evenly without brush marks
- Rainproof soon after application
- Highly weather resistant
- Excellent adhesion
- Wide range of colours available
- Saliva- and sweat-resistant according to DIN EN 71-3

Consumption: 60 – 80 ml/m² per coat

Gloss level: Satin matt

Colours:	0000 Colourless*	0300 Chestnut
	0101 Light oak	0700 Walnut
	0103 Antique oak	0710 Light walnut
	0150 Pine	0750 Mahogany
	0200 Limba	0850 Rosewood

Greying wood stains:	0706 Ice Stone
	0707 Grey Nature
	0708 Night Grey
	0709 Fog Grey

Other colours available on request.

Base for mixing:

* 0000 Colourless should never be applied as finish outdoors.

Pack size	VPE	Units per pallet (Product-No. W7111)
0.75 l tin	6	77 boxes
2.5 l tin	4	36 boxes
10 l drum	–	30 units
2.5 l tin	–	36 boxes
10 l drum	–	30 units
2.25 l tin	–	36 boxes
9 l drum	–	30 units

profilan®-top Dickschichtlasur

High build wood stain



Water-based high build wood stain for indoor and outdoor use

Transparent wood stain with high solids content. Preventive protection against mould and algae.

Fields of application: For all wooden elements, especially for timber components with dimensional stability, e.g. window frames, according to the guidelines for Institut für Fenstertechnik e.V. Rosenheim, Germany.

Properties:

- Good filling properties with very long-lasting weather protection
- Block resistant
- Very high level of transparency
- Silk gloss finish
- Suitability tested according to DIN EN 927-2
- Saliva- and sweat-resistant according to DIN EN 71-3

Consumption: 80 – 100 ml/m² per coat

Gloss level: Silk gloss

Colours:	0000 Colourless*	0103 Antique oak	0700 Walnut
	0005 Light grey	0150 Pine	0710 Light walnut
	0081 Opal white	0200 Limba	0750 Mahogany
	0101 Light oak	0300 Chestnut	0850 Rosewood

Other colours available on request.

Base for mixing: Do not use profilan®-top Base as „Colourless“ or to lighten the standard colours.

* 0000 Colourless should never be applied as finish outdoors.

Pack size	VPE	Units per pallet (Product-No. W7112)
0.75 l tin	6	77 boxes
2.5 l tin	4	36 boxes
10 l drum	–	30 units

0.675 l can	–	77 boxes
2.25 l can	–	36 boxes
9 l drum	–	30 units

profilan®-selva Holzöl | Oil



Water-based oil for wood used outdoors

Deeply penetrating surface protection based on vegetable oils.

Fields of application: For the initial coating and maintenance of wood used outdoors. Also suitable for use on both exotic and hard woods.

Properties:

- Water repellent and weather resistant
- Long open time
- Low odour
- Easy to apply without brush marks
- Pleasant to touch
- Saliva- and sweat-resistant according to DIN EN 71-3

Consumption: 60 – 80 ml/m² per coat

Colours:	0009 Nature*	0270 Bangkirai
	0210 Douglas fir	0800 Teak

Other colours available on request.

* 0009 Nature should never be applied as finish outdoors.

Pack size	VPE	Units per pallet (Product-No. W7215)
0.75 l tin	6	77 boxes
2.5 l tin	4	36 boxes
20 l drum	–	22 units

profilan[®]-opac Allwetterlack All-weather paint



Water-based, all-weather paint for wood used in- and outdoors

Highly weather-resistant paint with film protection against mould and algae.

Fields of application: For timber e.g. framework, balconies, wooden facades, window frames, doors, summerhouses, etc. After appropriate pre-treatment also suitable for treating brickwork, concrete, plaster, hard PVC, zinc and galvanised steel.

Properties:

- Highly opaque and diffusing
- Excellent adhesion on sound previous coats
- Effective against mould and algae
- Suitability certified according to DIN EN 927-2
- Block resistant
- Saliva- and sweat-resistant according to DIN EN 71-3

Consumption: 80 – 100 ml/m² per coat

Gloss level: Silk gloss

Colours:	1102 Sahara	7135 Agate
	1117 Yellow ochre	7140 Opal white
	3101 Red	8108 Bark brown
	3111 Crimson	8117 Chocolate
	3140 Sweden red	9105 Black
	6105 Fir green	9010 Birch white
	7130 Smoke grey	

Mixing colours metallic: DB 701

DB 702

DB 703

RAL 9006 White aluminium

RAL 9007 Grey aluminium

Other colours available on request.

Base for mixing:

Base A (White)

Base C (Transparent)

Base G (Metallic)

Pack size	VPE	Units per pallet (Product-No. W7114)
0.75 l tin	6	77 boxes
2.5 l tin	4	36 boxes
10 l drum	–	30 units
0.75 l tin	–	77 boxes
2.5 l tin	–	36 boxes
10 l drum	–	30 units
10 l drum	–	30 units
0.675 l tin	–	77 boxes
2.25 l tin	–	36 boxes
9 l drum	–	30 units

profilan[®]-Holzentgrauer



For cleaning, de-greying and brightening of weathered and grey timber used outdoors

Applications: For treating weathered and greyed soft and hard woods used outdoors such as garden furniture, terraces, balconies., etc.

Properties:

- Water-dilutable concentrate
- Low in odour and effective
- High cleaning power
- Thixotropic
- Easy to apply

Consumption: 150 – 200 ml/m² in concentrated form for de-greying;
30 – 40 ml/m² of the dilute solution (1:5 with water) for cleaning.

Colours: Pastel green

Pack size	VPE	Units per pallet (Product-No. W7217)
1 l bottle	15	24 boxes
5 l canister	3	30 boxes

impra® – Colour tinting centre

Select your favourite colour shade from several thousands of colours!
We can quickly and easily tint the perfect colour for your project!

Our range of brilliant and up to date colours will add a touch of individuality to your wood. Select your favourite shade from our wide spectrum of colours.

Your chosen colour is tinted on our impra® tinting centre with the highest possible accuracy. Our products are available in a wide range of conventional package sizes.

Thanks to the precision of our tinting equipment, we can tint the paint or wood stain to exactly the same colour shade even after many years.

